

Roofing Material	Cosy Cabin Size	Standard Price	Bushveld Cabin Size	Standard Price	Nutec Cabin Size	Standard Price	Amount of Windows
Corr Iron	2.4mx3.0m	15150,00	2.4mx3.0m	16320,00	2.4mx3.0m	16320,00	2ND2
Corr Iron	3.0mx3.0m	15730,00	3.0mx3.0m	17200,00	3.0mx3.0m	17200,00	2ND2
Corr Iron	3.6mx3.6m	17900,00	3.6mx3.6m	18860,00	3.6mx3.6m	18860,00	2ND2
Corr Iron	3.0mx4.8m	19940,00	3.0mx4.8m	20980,00	3.0mx4.8m	20980,00	2ND2
Corr Iron	6.0mx3.0m	22695,00	6.0mx3.0m	23650,00	6.0mx3.0m	23650,00	3ND2
Corr Iron	5.0mx4.0m	23340,00	5.0mx4.0m	25400,00	5.0mx4.0m	25400,00	3ND2
Corr Iron	6.0mx4.0m	25680,00	7.2mx3.0m	27720,00	6.0mx4.0m	27720,00	3ND2
Corr Iron	7.2mx3.0m	25125,00	6.0mx4.0m	29080,00	7.2mx3.0m	29080,00	4ND2
Corr Iron	7.2mx.3.6m	27720,00	7.2mx.3.6m	32460,00	7.2mx.3.6m	32460,00	4ND2
Corr Iron	6.0mx5.0m	30865,00	6.0mx5.0m	35000,00	6.0mx5.0m	35000,00	4ND2
			6.0mx6.0m	40970,00	6.0mx6.0m	40970,00	4ND2
			7.2mx6.0m	49370,00	7.2mx6.0m	49370,00	6ND2
All Cosy Cabin's include the Following: 1: Wall height 2.1m 2: 1.8mx1.9m Cottage pane, pine sliding door 3: Sisilation in the roof 4: Tongue and groove wall paneling 5: Tongue and groove floor planks 6: All construction timber S.A.B.S. S5 Grades 7: Outer walls treated with Waxsol 8: 1.5m Coverd Veranda 9: Galvenised Corr Iron roof sheeting unpainted 10: Instalation is done on bricks			All Log Wendy's include the Following: 1: Wall height 2.1m 2: 1.8mx1.9m Cottage pane, pine sliding door 3: Sisilation in the roof 4: 1/2 log profile wall paneling 5: Tongue and groove floor planks 6: All construction timber S.A.B.S. S5 Grades 7: Outer walls treated with Waxsol 8: 1.5m Coverd Veranda 9: Galvenised Corr Iron roof sheeting unpainted 10: Instalation is done on bricks		All Nutec Wendy's include the Following: 1: Wall height 2.1m 2: 1.8mx1.9m Cottage pane, pine sliding door 3: Sisilation in the roof 4: 6mm Nutec Sheeting joined with bishop strips 5: Tongue and groove floor planks 6: All construction timber S.A.B.S. S5 Grades 7: Nutec unpainted 8: 1.5m Coverd Veranda 9: Galvenised Corr Iron roof sheeting unpainted 10: Instalation is done on bricks		

Additional optional features you may want to consider:

	Double Paneling	Pitched Ceiling	Chromadek sheeting	Polytherm in walls
2.4mx3.0m	5054,00	1965,00	2184,00	2835,00
3.0mx3.0m	5615,00	2457,00	2496,00	3150,00
3.6mx3.6m	6740,00	3369,00	3159,00	3780,00
3.0mx4.8m	7300,00	3510,00	3120,00	4095,00
6.0mx3.0m	8420,00	4212,00	3744,00	4725,00
5.0mx4.0m	8425,00	4680,00	3744,00	4725,00
7.2mx3.0m	9540,00	4915,00	4368,00	5355,00
6.0mx4.0m	9360,00	5616,00	4680,00	5250,00
7.2mx.3.6m	10100,00	5896,00	4915,00	5670,00
6.0mx5.0m	10295,00	7020,00	5148,00	5775,00
6.0mx6.0m	11232,00	8424,00	6084,00	5796,00
7.2mx6.0m	12355,00	9828,00	7098,00	6930,00

Sizes and cost for Pine windows:

NE1 (0.5mx0.45m)	210,00
NE2 (0.5mx0.90m)	360,00
NE3 (0.5mx1.30m)	510,00
ND1 (0.8mx0.45m)	400,00
ND2 (0.8mx0.90m)	580,00
ND3 (0.8mx1.30m)	760,00
ND54 (1.5mx1.5m)	1225,00

Polytherm Specifications:

Polytherm made from 100% recycled white plastic bottles.

Safe as Houses Non-toxic, fire safe, and does not support rodents or bacterial/fungal growth. Benefits the Environment by reducing energy usage, and greenhouse gas emissions.

Fibre Composition Polytherm is extruded polyhester fibres, with inherent self extinguishing properties, which are made to the highest specifications.

Thermal Conductivity The thermal conductivity of Polytherm and Ecotherm is 0.057Wm°C, when tested in accordance with ISO 8301 at a mean temperature of 23°C

Odor Free Polytherm and Ecotherm has been tested to ASTM C1304 and has been found not to have any objectionable odor.

Dimensional Stability & Operational Temperature Polytherm will not shrink and are dimensionally stable in the temperature range of -30°C to the density of Polytherm 130°C

The moisture content of Polytherm and environment became damp. This is after exposure to high confirmed by the testing in humidity at elevated temperature (105°C accordance with ASTM C665 and 90% R.H.), in less than 0.2% by mass as is required by draft SANS 1381 - 1:2005 method 6.8. This test indicates that Polytherm will not cause damp problems when installed over ceilings

Cosy Cabins Terms and conditions:

- All final payments of units delivered are strictly **C.O.D.** and must be settled on site when the contractors arrive to finish the erection of the unit.
- You have a 10 year construction guarantee should any problems arise they will be dealt, with within a reasonable time frame, any breach of this agreement will result in the immediate removal of the unit, and you as the client will forfeit any deposits already paid.
- The 10 year construction guarantee is subject to the client having the unit serviced through our company at an additional cost annually, or alternatively purchasing the Waxsol from Cosy Cabins annually.
- Phoning and booking the service or purchasing annually is solely the clients responsibility, and the price will be determined yearly.
- Proof of either the service or purchase of the Waxsol must be retained by the client as Cosy Cabins may ask for the proof upon lodging of a complaint.
- Orders cancelled after a deposit has been paid, will be subject to a 20% handling fee.
- Orders are processed once conformation of deposit is received from the client.
- Prices are subject to change without any prior notice.
- Please note this is a summarised version of our terms and conditions, please see our website and Quote forms for all applicable terms and conditions.